

2025

MULE™ 4010 4x4



- TIMBERLINE GREEN
- DARK ROYAL RED



POWER

|                         |                                                                               |
|-------------------------|-------------------------------------------------------------------------------|
| Engine                  | 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled                          |
| Displacement            | 617cc                                                                         |
| Maximum Torque          | 34.7 lb-ft @ 2,500 rpm                                                        |
| Bore x Stroke           | 76.0 x 68.0mm                                                                 |
| Compression Ratio       | 10:3:1                                                                        |
| Fuel System             | DFI® with 34mm Mikuni throttle body                                           |
| Transmission            | Continuously Variable Transmission (CVT) with (H,L,N,R)                       |
| Final Drive             | Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock |
| Engine Braking          | No                                                                            |
| Alternator Output (max) | 23 amp                                                                        |

|                              |                                               |
|------------------------------|-----------------------------------------------|
| Rear Brakes                  | Drum                                          |
| Ground Clearance             | 6.9 in                                        |
| Fuel Capacity                | 6.3 gal                                       |
| Turning Radius               | 11.2 ft                                       |
| Cargo Bed Dimensions (LxWxH) | 46.3 x 51.6 x 11.4 in                         |
| Cargo Bed Load Capacity      | 800 lb                                        |
| Payload Capacity             | 1,327 lb                                      |
| Seating Capacity             | 2                                             |
| Towing Capacity              | 1,200 lb                                      |
| Lighting                     | (2) Halogen headlights, (2) tail/brake lights |

CAPABILITY

|                                 |                                                  |
|---------------------------------|--------------------------------------------------|
| Front Suspension / Wheel Travel | MacPherson Strut/3.9 in                          |
| Rear Suspension / Wheel Travel  | DeDion Axle/2.8 in                               |
| Front Tires                     | 23 x 11-10                                       |
| Rear Tires                      | 23 x 11-10                                       |
| Steering                        | Rack-and-pinion w/ Electric Power Steering (EPS) |
| Park Brake Type                 | Independent, mechanical drum                     |
| Front Brakes                    | Drum                                             |

DETAILS

|                |                                                                                                       |
|----------------|-------------------------------------------------------------------------------------------------------|
| Overall Length | 116.7 in                                                                                              |
| Overall Width  | 62.0 in                                                                                               |
| Overall Height | 75.8 in                                                                                               |
| Curb Weight    | 1,433.3 lb*                                                                                           |
| Wheelbase      | 73.6 in                                                                                               |
| Instruments    | Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter |
| Color Choices  | Timberline Green, Dark Royal Red                                                                      |
| Warranty       | Kawasaki STRONG 3-Year Limited Warranty                                                               |

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ 4000/4010 and MULE 4000/4010 TRANS™ Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of SAE J1194. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.