

2026

Z900RS SE ABS

Kawasaki
Let the Good Times Roll®



 METALLIC SPARK BLACK



POWER

Engine	4-stroke, 4-cylinder, DOHC, 16-valve, liquid-cooled
Displacement	948cc
Bore x Stroke	73.4 x 56.0mm
Compression Ratio	11.8:1
Maximum Horsepower	115.0 hp ¹ @ 9,300 rpm
Maximum Torque	73.0 lb-ft @ 7,700 rpm
Fuel System	DFI® with 36mm throttle bodies
Ignition	TCBI with Electronic Advance
Transmission	6-speed, return shift
Final Drive	Sealed chain
Electronic Rider Aids	Economical Riding Indicator, Electronic Cruise Control, Kawasaki TRaction Control (KTRC), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-Enhanced Chassis Orientation Awareness

PERFORMANCE

Front Suspension / Wheel Travel	41mm inverted telescopic fork with (12-way) adjustable compression and rebound (10-way) damping, spring preload (15-turn)/4.7
Rear Suspension / Wheel Travel	Horizontal back-link swingarm, Öhlins S46 shock with 30-position adjustable rebound damping and stepless spring preload adjustability/5.5 in

Front Tire	120/70-17
Rear Tire	180/55-17
Front Brakes	Dual 300mm discs with Brembo M4.32 monobloc four-piston calipers and ABS
Rear Brakes	Single 250mm disc with single-piston caliper and ABS

DETAILS

Frame Type	Trellis, high tensile steel
Rake/Trail	25.0° / 3.9 in
Overall Length	82.7 in
Overall Width	32.1 in
Overall Height	44.7 in
Ground Clearance	5.5 in
Seat Height	32.3 in
Estimated Dry Weight	434.4 lb**
Curb Weight	476.3 lb*
Fuel Capacity	4.5 gal
Wheelbase	57.7 in
Special Features	All-LED lighting, USB-C outlet, ERGO-FIT®, Smartphone Connectivity with available Voice Command and Turn-by-Turn Navigation via RIDEOLGY THE APP MOTORCYCLE***
Color Choices	Metallic Spark Black
Warranty	12 Month Limited Warranty

Scan with camera
to view videos,
key features
and more.



¹Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.
^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
^{**}Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
^{***}RIDEOLGY THE APP and all trademarks, registered trademarks, logos, and copyrights are the property of their respective owners. Voice command and navigation functions will be available only to users who have purchased a license for those functions. Feature availability may vary to meet individual markets.
¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit hawaii.kawasaki.com for full product details.