

2026

NINJA® 650

Kawasaki

Let the Good Times Roll®



- LIME GREEN
- METALLIC FLAT SPARK BLACK/METALLIC CARBON GRAY
- METALLIC MATTE WHITISH SILVER/
METALLIC FLAT SPARK BLACK
- METALLIC YELLOWISH GREEN/METALLIC SPARK BLACK



POWER		Front Brakes	Dual 300mm petal-type discs and 2-piston calipers (and ABS)
Engine	4-stroke, parallel twin, DOHC, 8-valve, liquid cooled	Rear Brakes	Single 220mm petal-type disc and single-piston caliper (and ABS)
Displacement	649cc	DETAILS	
Bore x Stroke	83.0 x 60.0mm	Frame Type	Trellis, high-tensile steel
Compression Ratio	10.8:1	Rake/Trail	24.0° / 3.9 in
Maximum Horsepower	67.0 hp ¹ @ 8,000 rpm	Overall Length	80.9 in
Maximum Torque	48.5 lb-ft @ 6,700 rpm	Overall Width	29.1 in
Fuel System	DFI® with dual 36mm Keihin throttle bodies	Overall Height	45.1 in
Ignition	TCBI with Electronic Advance	Ground Clearance	5.1 in
Transmission	6-speed	Seat Height	31.1 in
Final Drive	Sealed chain	Estimated Dry Weight	392.5 lb** (ABS), 390.3 lb** (non-ABS) 50-State Model; 390.3 lb** (ABS), 388.1 lb** (non-ABS) 49-State Model
Electronic Rider Aids	Kawasaki TRaction Control (KTRC), Anti-lock Brake System (ABS only)	Curb Weight	425.6 lb* (ABS), 423.4 lb* (non-ABS) 50-State Model; 423.4 lb* (ABS), 421.2 lb* (non-ABS) 49-State Model
PERFORMANCE		Fuel Capacity	4.0 gal
Front Suspension / Wheel Travel	41mm hydraulic telescopic fork/4.9 in	Wheelbase	55.5 in
Rear Suspension / Wheel Travel	Horizontal back-link with adjustable spring preload/5.1 in	Color Choices	Lime Green, Metallic Flat Spark Black/Metallic Carbon Gray, Metallic Matte Whitish Silver/Metallic Flat Spark Black, Metallic Yellowish Green/Metallic Spark Black
Front Tire	120/70 x 17	Warranty	12 Month Limited Warranty
Rear Tire	160/60 x 17		

Scan with camera to view videos, key features and more.

¹Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

^{**}Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit hawaii.kawasaki.com for full product details.